

SHIFTA



SHIFTA



TECHNICAL SPECIFICATIONS

The 300mm wide Shifta is a favourite amongst hire companies, with its lightweight aluminium frame it is portable and makes working on site far easier. The machine moves with your workspace allowing you to spend more time on the job and less time ferrying to and from site.

It comes with a 0.55kw drum motor. Extruded lightweight aluminium frame, rollers and heavy-duty chevron belt.

With a capacity of 60 tonnes per hour the Shifta is a real workhorse of a machine, designed to be used day in and day out. It will soon become a trusted and vital member of your team.

The 450mm Shifta is the older brother to the 300mm counterpart. It packs more of a punch with its 0.75kw motor, it can shift up to 90 tonnes per hour.

The same great technology has been expanded, due to popular demand the Shifta was increased in size to help account for the additional requirements of our customers. The 450mm wide Shifta has the same aluminium frame, drum motor, rollers and heavy-duty chevron belt to make sure your loads are dealt with easily.

The 450mm Shifta has a proven record and is now available internationally.

SHIFTA 300 WIDE	MODEL	WEIGHT	MAX PAYLOAD	MAX ANGLE	CAPACITY PER HOUR
	3.2 metre	103kg	150kg	55	60 T
	4.4 metre	126kg	150kg	55	60 T
	5.4 metre	140kg	150kg	55	60 T

SHIFTA 450 WIDE	MODEL	WEIGHT	MAX PAYLOAD	MAX ANGLE	CAPACITY PER HOUR
	3.2 metre	116kg	200kg	55	90 T
	4.4 metre	160kg	200kg	55	90 T
	5.4 metre	180kg	200kg	55	90 T

The UK's number one conveyor of rubble, aggregates and soils.

With its aluminium construction, this lightweight machine is now even more portable than before. The Shifta has a tough rubber troughed belt, a three-phase two-speed three phase (110v input) motor and a portable hopper that is large enough to convey bulky material. The ideal machine for moving material in difficult terrain with an incline up to 50 degrees. Shifta moves aggregate quickly and efficiently. The preferred choice for shifting large amounts of material on building sites all over the UK.

MAIN FEATURES

AVAILABLE IN 3.2, 4.4 OR 5.4M LENGTHS



HOPPER EASILY DETACHED



LIGHTWEIGHT AND EASY TO MANOEUVRE



150KG MAXIMUM PAYLOAD



28 METERS PER MINUTE SPEED



AVAILABLE IN 300MM AND 450MM WIDTHS

